

Speciality Photo Papers

Photo Pearl Premium 310gsm OLM-070



Description:

A premium, luxurious Ultra White RC inkjet paper that will do any image justice. It has a slightly textured stippled surface to give a subtle silky sheen to your finished image. It has a Microporous coating and is touch dry when printed and water resistant.

Applications include; Photography, portrait printing, posters and exhibition printing.

| | |
|---|---|
| Weight (GSM) | 310 |
| Base Material | Resin Coated |
| Coating Type | Microporous Pearl |
| Surface Texture | Slightly textured pearl |
| Thickness (Microns / inches) | 299 / 0.012 |
| Whiteness (CIE) | 145 |
| Brightness (TAPPI) | |
| OBA content | Yes |
| pH | 7.5-9.5 |
| Sheets Size: Availability / sheets per box | DIN A4 / A3 / A3+ / A2 - 50 sheets (US sizes available on request) |
| Roll Size: Availability / Length / Core size | 17" (432mm) / 24" (610mm) / 44" (1118mm) - 25m - 3" core |
| Printer/Ink Compatibility | Compatible with all commercial thermal and piezo inkjet printers using water-based dye and pigment-based inks such as Epson, Canon and Hewlett-Packard |
| Recommended printer Settings | Photo black inks with generic media setting of 'Photo Semi-gloss / Lustre' / 'Premium Photo paper Semi-matte' or similar. ICC colour profiles are available from the website. |

Directions for Use:

Paper Handling:

- Avoid touching the coated surface of the paper before and after printing, and wear cotton gloves if necessary.
- Avoid exposure to high temperatures, high levels of humidity and moisture. These factors can affect the drying time of some Olmec™ products.

Paper Storage:

- Remove prints from the tray after printing; do not allow them to be stacked.
- Prints should be allowed to dry in air, preferably left uncovered for 24 hours to allow the residual liquid from the inks to evaporate.
- In cases where stacking is unavoidable, a paper inter leaf should be placed between each print.

Conditions of Use:

- Where possible, all paper should be stored and used within the following range of environmental conditions:
Temperature = 10° - 35° Centigrade
Relative Humidity = 30% - 80%
- Unused paper should be stored in its original packaging, out of direct sunlight under normal climatic conditions.



Olmec™ papers are manufactured and distributed by Innova Art. All recommendations and product indications are for your guidance, and are subject to our test criteria.

PROFESSIONAL PHOTOGRAPHIC INKJET PAPER

www.innovaart.com